



## Vitowell – Comfort Cylinders storage water heaters



### Hot water for the entire house

The VITOWELL Comfort range of electric storage water heaters, with capacities ranging from 30 to 100 liters, is an excellent choice for providing hot water throughout your home. Durable, safe, and designed for high hot water comfort, this range is perfectly suited to meet a variety of domestic needs. The versatile design allows for easy installation, whether horizontally or vertically.

### Features

- + Long lasting tank with corrosion-resistant Ti+ enamel coating
- + Large magnesium anode for superior corrosion protection
- + Flexible horizontal or vertical installation without adjustments
- + High performance stainless steel heating element with Ti enamel coating
- + Anti-bacterial water inlet and copper valve for enhanced hygiene
- + Advanced safety features: overheat protection, dry-heat prevention, and overpressure control
- + User-friendly indicators: Power ON and Heating ON for convenience

## Vitowell – Comfort Cylinders

VITOWELL Comfort Cylinders water heater with large capacity is durable and safe, providing hot water comfort for everyone in the house.

|                          |     | C2-VH 30                           | C2-VH 50                           | C2-VH 80                           | C2-VH 100                          |
|--------------------------|-----|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Capacity                 | L   | 27                                 | 45                                 | 80                                 | 100                                |
| Rated Power              | W   | 1500                               | 1500                               | 1500                               | 1500                               |
| Rated Voltage            |     | 220-240                            | 220-240                            | 220-240                            | 220-240                            |
| Rated Frequency          | Hz  | 50/60                              | 50/60                              | 50/60                              | 50/60                              |
| Heating Element          |     | Ti enamelled stainl. steel         | Ti enamelled stainl. steel         | Ti enamelled stainl. steel         | Ti enamelled stainl. steel         |
| Dimensions (DxH)         | mm  | 340x593                            | 385x711                            | 385x1030                           | 450x915                            |
| Net weight               | Kg  | 14.79                              | 18.3                               | 26.31                              | 28.57                              |
| Temperature range        | °C  | 30-75                              | 30-75                              | 30-75                              | 30-75                              |
| Max. working pressure    | Mpa | 0.75                               | 0.75                               | 0.75                               | 0.75                               |
| Degree of protection     |     | IPX4                               | IPX4                               | IPX4                               | IPX4                               |
| Energy Efficiency Rating |     | C                                  | C                                  | C                                  | C                                  |
| Indicators               |     | -                                  | Power ON & Heating ON              | Power ON & Heating ON              | Power ON & Heating ON              |
| Protection               |     | Over heat, dry heat, over pressure | Over heat, dry heat, over pressure | Over heat, dry heat, over pressure | Over heat, dry heat, over pressure |
| Max. temperature         | °C  | 101                                | 100                                | 100                                | 360                                |
| Inner tank               |     | Ti.+ enamelled                     | Ti.+ enamelled                     | Ti.+ enamelled                     | Ti.+ enamelled                     |
| Outer Cladding           |     | SPCC                               | SPCC                               | SPCC                               | SPCC                               |
| Connection               |     | Cable 1.5m (w/o plug)              | Cable 1.5m (w/o plug)              | Cable 1.5m (w/o plug)              | Cable 1.5m (w/o plug)              |
| Mounting                 |     | Vertical/horizontal hang mount     | Vertical/horizontal hang mount     | Vertical/horizontal hang mount     | Vertical/horizontal hang mount     |
| Water Connection Size    |     | G1/2                               | G1/2                               | G1/2                               | G1/2                               |
| Carton Size              | mm  | 418x388x67                         | 458x434x793                        | 458x434x1125                       | 528x498x997                        |
| Certification            |     | Region specific                    | Region specific                    | Region specific                    | Region specific                    |